

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY

EL654514190US

(51) International Patent Classification ⁷ : H04B 1 /00	A2	(11) International Publication Number: WO 00/04659 (43) International Publication Date: 27 January 2000 (27.01.00)
(21) International Application Number: PCT/EP99/04665 (22) International Filing Date: 5 July 1999 (05.07.99) (30) Priority Data: 9815392.7 15 July 1998 (15.07.98) GB (71) Applicant (for all designated States except US): TELEFONAKTIEBOLAGET LM ERICSSON [SE/SE]; S-126 25 Stockholm (SE). (72) Inventor; and (75) Inventor/Applicant (for US only): BRISTOW, Robert, Owen [GB/GB]; 9 Sonning Close, Basingstoke, Hampshire RG22 5JJ (GB). (74) Agent: O'CONNELL, David, Christopher; Haseltine Lake & Co., Imperial House; 15-19 Kingsway, London WC2B 6UD (GB).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>Without international search report and to be republished upon receipt of that report.</i>
(54) Title: RADIO COMMUNICATIONS UNIT		
(57) Abstract <p>There is described a radio communications system, including a unit which is able to communicate over a radio communications network such as a satellite or cellular system, and is also able to communicate with a device such as a portable handset over a short range radio link. In order to avoid potentially troublesome interference on the communications path with the communications network, the unit is able to detect the strength of signals received on the short range radio link, and alert the user if those signals are such as to be a potential source of interference.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon	KR	Republic of Korea	PL	Poland		
CN	China	KZ	Kazakhstan	PT	Portugal		
CU	Cuba	LC	Saint Lucia	RO	Romania		
CZ	Czech Republic	LI	Liechtenstein	RU	Russian Federation		
DE	Germany	LK	Sri Lanka	SD	Sudan		
DK	Denmark	LR	Liberia	SE	Sweden		
EE	Estonia			SG	Singapore		

RADIO COMMUNICATIONS UNITTECHNICAL FIELD

5 This invention relates to a radio communications unit, and more particularly to a unit which is able to communicate over a radio communications network such as a satellite or cellular system, and is also able to communicate with a device such as a portable handset over a short range radio link.

BACKGROUND OF THE INVENTION

10 A potential disadvantage with the use of units of the general type mentioned above is that there may be interference signals appearing on the frequency at which the unit communicates with the communication network such as the satellite or cellular network. In
15 particular, signals received on the short range radio link may be a source of such interference.

A problem therefore arises with such units as to how to avoid interference of this type.

SUMMARY OF THE INVENTION

20 In accordance with the invention, interference on the communications path with the communications network is avoided by detecting the strength of signals received on the short range radio link, and alerting the user if those signals are such as to be a potential
25 source of interference.

In particular, a unit in accordance with the invention comprises a first transceiver for communicating over a communications network such as a cellular or satellite system, and a second transceiver
30 for communicating with a device such as a portable handset over a short range radio link. The unit further comprises means for detecting the signal strength of signals received over the short range radio link, and means for comparing that signal strength with
35 a predetermined threshold. The unit further comprises means for alerting the user in the event that the

threshold is exceeded.

This has the advantage that communications over the short range radio link can then be suspended to avoid the possibility of such interference.

5 BRIEF DESCRIPTION OF DRAWING

Figure 1 is a block schematic diagram of a system in accordance with the invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENT

10 For a better understanding of the present invention, and to show how it may be put into effect, reference will now be made, by way of example, to the accompanying drawing.

Figure 1 shows a system in accordance with the invention.

15 The system 2 includes a first antenna 4, connected to transceiver circuitry 6, for communication over a radio communications network. In one preferred embodiment of the invention, the transceiver circuitry 6 is adapted for communication over a conventional
20 cellular network, although it may equally be adapted for communication over a satellite network, or indeed any other radio communications network.

The unit 2 further comprises a second antenna 8, and transceiver circuitry 10, for communication over a
25 short range radio link. Figure 1 further shows a portable handset 12, having its own antenna 14, for communication over the same link with the unit 2. Although the invention is described herein with reference to communication over the short range radio
30 link with a portable handset 12, it will be appreciated that this device may be any device which is located remotely from the system 2, or at least is moveable relative thereto.

For example, the unit 2 may be adapted for
35 communication over a Globalstar satellite network, transmitting on channels in the band from 1610-1627

MHz, and receiving signals from the satellite on channels in the band from 2480-2500 MHz. The short range link can advantageously operate in the internationally recognised ISM band from 2400-2480 MHz, both to transmit and to receive.

The system 2 includes a satellite baseband and control module 7, and a short range link baseband and control module 11. These modules 7, 11 receive data from the respective transceiver circuits 6, 10 and transmit them to the other transceiver circuit via the other module. Moreover, the modules 7, 11 send tuning and power control signals to their respective transceiver circuit 6, 10.

The system 2 further comprises a controlling and interfacing unit 16, which controls the overall operation of the device, and, in particular, sends and receives signals to and from the transceiver units 6, 10.

The control unit 16 includes means for determining the signal strengths of signals received from the remote unit 12 at the transceiver circuitry 10. The object is to determine when the signal from the remote unit 12, received at the system main unit 2, is sufficiently strong to provide a possible source of interference for the reception of signals at the transceiver 6. This may be achieved in different ways.

As a first example, a measurement may be made of the strength of the signal received from the remote unit 12 at the short range receiver circuit 10.

As a second alternative, a measurement may be made of the signal strength of the signal from the remote unit 12 in the main receiver unit 6.

As a third alternative, a measurement may be made in the main receiver unit 6 of the strength of a noise signal at the frequency which that receiver unit is using for reception of signals from the communications

network.

In Figure 1, the control unit 16 is shown as having inputs from both transceiver circuits 6, 10. However, depending on which of these alternatives is used, only one of the inputs may be required.

In the case of this third alternative, it can be determined that any received noise signal is a result of transmissions from the remote unit 12 in different ways.

As a first example, a correlation between the occurrence of a noise signal and a known time at which the remote unit 12 is transmitting may be used as an indication that it is the remote unit 12 which is the source of the noise signal.

As a second example, a correlation between transmissions from the remote unit 12 on particular frequencies, and the occurrence of noise in the receiver unit 6, may be used as an indication that transmissions from the remote unit 12 are the source of the noise signal in the receiver unit 6.

As a third example, signals transmitted from the remote unit 12 may include a code modulated thereon in any convenient way (for example, AM, PM or FM), and the receiver unit 6 may include means for demodulation of such a code for use as an indication that it is transmissions from the remote unit 12 which are the source of noise signals received in the receiver unit 6.

In any case, the detected signal strength is compared with a predetermined threshold, set in each case at a level which is determined on the basis of a signal strength which may be a troublesome source of interference in the receiver unit 6.

If it is determined by the control unit 16, on the basis of signal strength measurements taken on signals received at the receiver unit 6 or the receiver unit

10, as described above, an alerting signal is then generated. In a preferred embodiment of the invention, this alerting signal is generated in the controlling unit 16, sent via the short range link baseband and control module 11 and the transceiver circuit 10, and transmitted across the short range radio link to the remote unit 12. In the remote unit 12, such a signal is converted into an appropriate form of warning to the user of the device. For example, the warning may take the form of an audible message, stored in the remote unit and played back in response to the receipt of an alerting signal, or a visual message, displayed on the display device of the remote unit in response to the receipt of the alerting signal, for example.

Alternatively, since any warning is likely to be issued when the remote unit 12 is close to the main unit 2, it may be acceptable, and technically simpler, for the warning to be generated in the main unit.

Alternatively or, preferably, in addition, the controlling unit can issue a command to prevent further interfering transmissions from the remote unit 12 to the receiver unit 10. For example, if the signal strength of transmissions from the remote unit 12, received at the receiver unit 10, is sufficiently high to be a potential source of interference, this is likely to be because the remote unit 12 is very close to the system main unit 2. In such an event, it is highly probable that it will be acceptable to switch to an infrared communications link between the remote unit 12 and system main unit 2. To that end, in the preferred embodiment of the invention, the system main unit 2 includes an infrared transceiver 18, and the remote unit 12 includes an infrared transceiver 20.

As an alternative, the alerting message to the user may for example request that the user discontinue the use of the radio link and instead switch to a wired

communication from the remote unit to the system main unit. Again, this may be acceptable if the reason for the interference is that the remote unit has moved close to the system main unit.

5 As a further alternative, the main unit 2 and remote unit 12 may include alternative transceivers, allowing communications to be switched to an alternative radio frequency band, which reduces the possibility of interference.

10 In accordance with a preferred embodiment of the present invention, the circuitry described above may also be used to detect possible sources of interference originating other than in the radio frequency transmissions with the system main unit over the short
15 range link. For example, transmissions over the radio communications network might suffer interference from other communications users, or even from non-communications sources of radio frequency signals such
as microwave ovens.

20 The short range receiver unit 10 in the system main unit 2 is arranged to receive signals on channels which could potentially contain unwanted interference signals. Where the short range radio link between the system main unit 2 and the remote unit 12 is a
25 frequency hopped system, the receiver unit 10 may hop to channels which are blocked by strong interference. In this event, the signal level is still measured, and used as a criterion to warn the user. If a strong signal occurs at a time when the error rate on the
30 short range radio link is high, it can be inferred that the source of the signal is an unwanted third party interferer.

35 Alternatively, the receiver unit 6 in the system main unit 2 could be arranged to select channels which are more likely to be interfered with, and could then correlate the received noise signal with that on other

channels. This would allow an inference to be made about the source of interference.

There is thus described a system which allows the possibility of interference on the main communications link to be reduced.

5

CLAIMS

1. A communications device, comprising:
a first transceiver for communicating over a first communication network;
5 a second transceiver for communicating with a remote unit;
means for detecting signal strengths of potentially interfering signals; and
means for providing an alert signal if the
10 detected signal strengths exceed a predetermined threshold.
2. A communications device as claimed in claim 1, further comprising means for detecting signal strengths of signals received from the remote unit in
15 the first transceiver.
3. A communications device as claimed in claim 1, further comprising means for detecting signal strengths of signals received from the remote unit in the second transceiver.
- 20 4. A communications device as claimed in claim 1, further comprising means for detecting signal strengths of noise signals, caused by transmissions received from the remote unit, in the second transceiver.
- 25 5. A communications device as claimed in claim 4, further comprising means for identifying times at which transmissions are being received from the remote unit, and means for identifying times at which the detected signal strengths of noise signals in the
30 second transceiver exceed a specified level, and means for comparing the identified times.
- 35 6. A communications device as claimed in claim 4, further comprising means for identifying times at which transmissions are being received from the remote unit on one or more specified frequencies, and means for identifying times at which the detected signal

strengths of noise signals in the second transceiver exceed a specified level, and means for comparing the identified times.

5 7. A communications device as claimed in claim 4, further comprising means for detecting in the second transceiver a code modulated onto transmissions from the remote unit.

10 8. A communications device as claimed in any preceding claim, comprising means for generating the alerting signal and transmitting it to the remote unit.

9. A communications device as claimed in any preceding claim, further comprising an infrared transceiver, for communicating with the remote unit when an alert signal is generated.

15 10. A communications system, comprising a communications device and a remote unit, the communications device comprising:

 a first transceiver for communicating over a first communication network;

20 a second transceiver for communicating with the remote unit;

 means for detecting signal strengths of potentially interfering signals; and

25 means for providing an alert signal if the detected signal strengths exceed a predetermined threshold,

 and the remote unit comprising a third transceiver for communicating with the communications device.

30 11. A communications system as claimed in claim 10, wherein the communications device comprises means for transmitting the alert signal to the remote unit.

35 12. A communications system as claimed in claim 11, wherein the remote unit comprises means for storing an audible message and means for playing back the stored audible message in response to a received alert signal.

13. A communications system as claimed in claim 11, wherein the remote unit comprises means for displaying a visual message in response to a received alert signal.

5 14. A communications system as claimed in claim 11, wherein the remote unit comprises means for receiving an alert signal, and for ceasing further radio transmissions to the communications device in response thereto.

10 15. A communications system as claimed in claim 14, wherein the communications device and the remote unit each comprise an infrared transceiver, and further comprising means for switching further transmissions to the infrared transceivers in response to an alert
15 signal.

THIS PAGE BLANK (USPTO)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
27 January 2000 (27.01.2000)

PCT

(10) International Publication Number
WO 00/04659 A3

(51) International Patent Classification⁷: H04B 1/38, 17/00

(21) International Application Number: PCT/EP99/04665

(22) International Filing Date: 5 July 1999 (05.07.1999)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
9815392.7 15 July 1998 (15.07.1998) GB

(71) Applicant (for all designated States except US): TELEFONAKTIEBOLAGET LM ERICSSON [SE/SE]; S-126 25 Stockholm (SE).

(72) Inventor; and

(75) Inventor/Applicant (for US only): BRISTOW, Robert, Owen [GB/GB]; 9 Sonning Close, Basingstoke, Hampshire RG22 5JJ (GB).

(74) Agent: O'CONNELL, David, Christopher; Haseltine Lake & Co., Imperial House, 15-19 Kingsway, London WC2B 6UD (GB).

(81) Designated States (national): AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

(88) Date of publication of the international search report:
11 October 2001

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

RECEIVED
NOV 13 2001
Technology Center 2600

(54) Title: RADIO COMMUNICATIONS UNIT

(57) Abstract: There is described a radio communications system, including a unit which is able to communicate over a radio communications network such as a satellite or cellular system, and is also able to communicate with a device such as a portable handset over a short range radio link. In order to avoid potentially troublesome interference on the communications path with the communications network, the unit is able to detect the strength of signals received on the short range radio link, and alert the user if those signals are such as to be a potential source of interference.

WO 00/04659 A3

THIS PAGE BLANK (USPTO)

INTERNATIONAL SEARCH REPORT

 International Application No.
 PCT/EP 99/04665

 A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 H04B1/38 H04B17/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

 Minimum documentation searched (classification system followed by classification symbols)
 IPC 7 H04B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No
A	DE 35 28 886 A (SIEMENS AG) 19 February 1987 (1987-02-19) abstract column 2, line 41 - line 60 column 3, line 55 - column 4, line 38 claim 3 figure 1	1-15
A	WO 92 10046 A (LIGHT IDEAS INC) 11 June 1992 (1992-06-11) abstract figure 3	9, 15

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"Z" document member of the same patent family

Date of the actual completion of the international search

15 October 1999

Date of mailing of the international search report

25/10/1999

Name and mailing address of the ISA

 European Patent Office, P.O. 6818 Pattemaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl.
 Fax: (+31-70) 340-3016

Authorized officer

Tzimeas, K

THIS PAGE BLANK (USPTO)

INTERNATIONAL SEARCH REPORT


International Application No.

PCT/EP 99/04665

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 3528886	A	19-02-1987	NONE	
WO 9210046	A	11-06-1992	AU 8850291 A	25-06-1992

THIS PAGE BLANK (USPTO)

1 / 1



500 Rec'd PTO 10 JAN 2001

THIS PAGE BLANK (USPTO)